

## REINFORCED DISCONNECT TERMINALS

for copper cables












RKF-F  
BKF-F  
GK-F










- Manufactured from brass strip
- Electrolytically tin plated
  - fully reinforced with copper sleeve, funnel entry
  - The operating temperature range is  $-20^{\circ}\text{C}$  to  $+105^{\circ}\text{C}$  (Surge  $+110^{\circ}\text{C}$ )
  - Recommended crimping tools are shown on pages 92 to 111, 144, 183.

female connectors, fully reinforced with copper sleeve

PA6.6 insulated terminals

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RKF-F 305	2,8 x 0,5	3.500/100
	 RKF-F 308	2,8 x 0,8	3.500/100
	 RKF-F 405	4,8 x 0,5	3.000/100
1,5÷2,5 (16÷14)	 RKF-F 408	4,8 x 0,8	3.000/100
	 RKF-F 608	6,35 x 0,8	2.500/100
	 BKF-F 405	4,8 x 0,5	3.000/100
4÷6 (12÷10)	 BKF-F 408	4,8 x 0,8	3.000/100
	 BKF-F 608	6,35 x 0,8	2.000/100
	 GK-F 608	6,35 x 0,8	1.500/100

PA6.6 fully insulated terminals




Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RKF-F 405P	4,8 x 0,5	2.500/100
	 RKF-F 408P	4,8 x 0,8	2.000/100
1,5÷2,5 (16÷14)	 RKF-F 608P	6,35 x 0,8	1.000/100
	 BKF-F 405P	4,8 x 0,5	2.000/100
4÷6 (12÷10)	 BKF-F 408P	4,8 x 0,8	2.000/100
	 BKF-F 608P	6,35 x 0,8	1.000/100
4÷6 (12÷10)	 GK-F 608P	6,35 x 0,8	1.000/100

RKF  
BKF  
GKF





- Manufactured from brass strip
- Electrolytically tin plated
  - fully reinforced with copper sleeve, funnel entry
  - The operating temperature range is  $-20^{\circ}\text{C}$  to  $+105^{\circ}\text{C}$  (Surge  $+110^{\circ}\text{C}$ )
  - Recommended crimping tools are shown on pages 92 to 111, 144, 183.





male connectors, fully reinforced with copper sleeve - PA6.6 insulated terminals

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RKF-M 608	6,35 x 0,8	3.000/100
1,5÷2,5 (16÷14)	 BKF-M 608	6,35 x 0,8	2.500/100
4÷6 (12÷10)	 GKF-M 608	6,35 x 0,8	1.000/100

male/female connectors, fully reinforced with copper sleeve - PA6.6 insulated terminals

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RKF-FM 608	6,35 x 0,8	1.500/100
1,5÷2,5 (16÷14)	 BKF-FM 608	6,35 x 0,8	1.500/100

bullet and socket connectors  
fully reinforced with copper sleeve  
PA6.6 insulated terminals

Cond. Size sqmm (AWG)	Ref.	Ø mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RKF-BM 4	4	2.500/100
	 RKF-BF 4	4	1.000/100
1,5÷2,5 (16÷14)	 BKF-BM 4	4	2.000/100
	 BKF-BF 4	4	800/100