

QUICK DISCONNECTS


File No.: E70188 LR20812

Female, Fully-insulated with funnel-entry copper sleeve

Tape on Reel Only

Cable Size sq. mm.	Part No	W	E	Mating Tab Thickness
0.25-1.65	FLVZDF1.25-187A-5*	5.0	6.0	0.5
	FLVZDF1.25-187A-8*	5.0	6.0	0.8
1.04-2.63	FLVZDF2-187A-5*	5.0	6.0	0.5
	FLVZDF2-187A-8*	5.0	6.0	0.8
0.25-1.65	FLVZDF1.25-250A	6.6	7.8	0.8
1.04-2.63	FLVZDF2-250A	6.6	7.8	0.8

* Without wire stop



Female, Fully-insulated Nylon

Cable Size sq. mm.	Part No	W	E	Mating Tab Thickness
0.25-1.65	LNDDF 1.25-110T-5	2.8	6	0.5
0.25-1.65	LNDDF 1.25-110T-8	2.8	6	0.8


Female, Nylon part-insulated

Cable Size sq. mm.	Part No	W	E	Mating Tab Thickness
0.25-1.65	FNDDF 1.25-110A-5	2.8	6	0.5
0.25-1.65	FNDDF 1.25-110A-8	2.8	6	0.8
0.25-1.65	FNDDF 1.25-187A-5	4.8	6	0.5
0.25-1.65	FNDDF 1.25-187A-8	4.8	6	0.8
0.25-1.65	FNDDF 1.25-250A	6.6	7.8	0.8
1.04-2.63	FNDDF 2-187A-5	4.8	6	0.5
1.04-2.63	FNDDF 2-187A-8	4.8	6	0.8
1.04-2.63	FNDDF 2-250A	6.6	7.8	0.8
2.63-6.64	FNDDF 5.5-250A	6.6	7.8	0.8



Male, Vinyl-insulated with copper sleeve

Cable Size sq. mm.	Part No	W	E	Mating Tab Thickness
0.25-1.65	FVDDM1.25-250	6.3	8.0	0.8
1.04-2.63	FVDDM2-250	6.3	8.0	0.8
2.63-6.64	FVDDM5.5-250	6.3	8.0	0.8



PIGGYBACKS

Vinyl-insulated with copper sleeve

Cable Size sq. mm.	Part No	W		E		Material Thickness
		W1	W2	E1	E2	
0.25-1.65	FVDDFM1.25-250A	6.6	6.3	7.8	8.0	0.4
1.04-2.63	FVDDFM2-250A	6.8	6.3	22.2	7.8	0.4
	FVDDFM2-250B					

