



File No.:  E42024  LR20812



**STYLE A**  
Uninsulated



**STYLE B**  
Straight Vinyl Insulation  
Prefix VWS



**STYLE C**  
Straight Vinyl Insulation  
+ A.V. Sleeve  
Prefix VDWS



**STYLE D**  
Flared Vinyl Insulation  
Prefix FVWS



**STYLE E**  
Flared Vinyl Insulation  
+ A.V. Sleeve  
Prefix FVDWS



**STYLE G**  
Flared Nylon Insulation  
+ A.V. Sleeve  
Prefix FNDWS




**STYLE H**  
Funnel-Entry Vinyl  
Insulation Prefix FVXWS  
Available Tape on Reel  
Only - Suffix TOR

Cable size 0.2-0.5 sq. mm.				Styles Available
Dimensions				
Part No	Stud Size	B	F	
0.5-2	2.2	5.2	5.8	A
0.5-3	3.2	5.2	5.8	A B C
0.5-3.7	3.7	6.6	7.7	A B C
0.5-4	4.3	6.6	7.7	A B C
0.5-5	5.3	8.0	7.0	A B C

Cable size 0.25-1.65 sq. mm.				Styles Available
Dimensions				
Part No	Stud Size	B	F	
1.25-2	2.2	5.5	4.0	A D
1.25-3	3.2	5.5	4.0	A B C D E G H
1.25-L3	3.2	8.0	7.0	A D
1.25-3.7	3.7	5.5	4.0	A B C D E G H
1.25-M3	3.7	6.6	6.3	A B C D E G H
1.25-4	4.3	8.0	7.0	A B C D E G H
1.25-M4	4.3	6.6	6.3	A B C D E G H
1.25-5	5.3	8.0	7.0	A B C D E G H
1.25-6	6.4	11.6	11.1	A B C D E G H
1.25-8	8.4	11.6	11.1	A D H
1.25-10	10.5	13.6	13.9	A D
1.25-12	13	16.5	9.5	A D

Cable size 1.04-2.63 sq. mm.				Styles Available
Dimensions				
Part No	Stud Size	B	F	
2-S2	2.2	6.4	4.3	A D G
2-3	3.2	8.5	7.8	A B D G H
2-S3.3	3.2	6.4	4.3	A B C D E G H
2-S3	3.7	6.6	6.3	A
2-M3	3.7	6.4	4.3	A B C D E G H
2-4	4.3	8.5	7.8	A B C D E G H
2-M4	4.3	6.6	6.3	A B C D E G H
2-5	5.3	9.5	11.0	A B C D E G H
2-M5	5.3	8.5	7.8	A B C D E G H
2-6	6.4	12.0	11.0	A B D
2-8	8.4	12.0	11.0	A D
2-10	10.5	13.6	13.9	A D
2-12	13	19.0	16.7	A D
2-16	17	27.0	21.2	A D
2-20	21	27.0	21.2	A D

Cable size 2.64-6.6 sq. mm.				Styles Available
Dimensions				
Part No	Stud Size	B	F	
5.5-3	3.2	9.5	8.3	A D
5.5-S3	3.7	7.2	5.9	A B C D E G H
5.5-4	4.3	9.5	8.3	A B C D E H
5.5-S4	4.3	7.2	5.9	A D G
5.5-5	5.3	9.5	8.3	A B C D E G H
5.5-S5	5.3	13.2	9.0	A B D
5.5-6	6.4	12.0	13.0	A B D E G H
5.5-S6	6.4	13.2	9.0	A B C D E H
5.5-8	8.4	15.0	13.7	A B D E
5.5-S8	8.4	11.6	11.1	A B D E G
5.5-10	10.5	15.0	13.7	A D
5.5-12	13	19.2	16.0	A D
5.5-16	17	32.0	25.3	A D
5.5-20	21	32.0	25.3	A D



REFER TO PAGES 22-23 FOR SUITABLE TOOLING

\*Some of the above are available as right angle and fork terminals

-Please contact our sales office